


Please read this manual carefully before installing and using the spots. Do this for your own safety and to prevent damage of the product. This manual is applicable to the LED (veranda) recessed spots. The set is delivered ready for use with the amount of spots you selected, including 5 meters cable per spotlight, 1 transformer with a connector. If you want to connect a Somfy system on the spots, then you will need a Somfy io receiver and a Somfy io remote control. Attention: These are not supplied as standard.

*This manual in your own language?
Or do you need another variant?
Scan the QR code.*




1




First, check whether all the parts are contained in the box, and test the set before installing it in its permanent place.

2




Drill the holes, size 42 mm, at the desired place. Next, position the wiring of the LED spots on the desired location. Place the LED spots in the drill holes. Now push up both spirals and position the spotlight.

3




Subsequently, link all the spots to the connector. The plugs should all be linked to the connector, as the system is connected in series. If the connector contains more ports than the amount of installed spots, please place a jumper (black jumper) in the remaining opening(s). Jumpers will be provided in the box (depending on the amount of spots and the type of connector).

4



Next, connect the Somfy Receiver on the transformer. 1-10V of the Somfy Receiver needs to be connected on the 1-10V of the transformer. Brown on negative (-) and blue on positive (+). Subsequently, you can connect the OUT (230V) of the Somfy Receiver on the PRI part of the transformer. Brown on L and blue on N. The green cable is not necessary to be connected. At last, connect the IN (230V) of the Somfy receiver on the main current. We recommend to switch off the branch circuit beforehand. Attention: the buttons 3, 5 and 6 needs to be switched on.

5



When the io-receiver is connected to the transformer, select the appropriate channel. Then press both arrows on the remote until the spotlights turns on, then press the PROG button on the back of the remote once. The lighting is now connected.

Your lightening is now ready for use. We wish you the best of luck with your purchase.